

MODEL D6073 & D6073x: SIDELOADER TUCKAWAY® LIFTERS

This TuckAway[®] model was developed specifically for sideloaders, with an extra long arc of motion to dump over a variety of sill heights. The D6073 series is available in several lengths to suit your application perfectly.

Perkins

Features and Benefits

The performance you demand requires a serious machine with all the refinements that you've come to expect from the leader in the waste handling industry.

- All new, powerful 27k Helical Actuator
- Available in three different sizes to best suit your application
- Pick-up cart both on and off the curb with back-saving cart grabbing action
- Featuring TuckAway lifter performance, dumps high & deep for maximum productivity
- Minimal greasing for less maintenance
- Spring loaded lower latch is easy on cart surfaces
- UHMW upper saddle prevents scratches on carts
- ISO 9001 manufacturer
- National Service technicians for product support
- Fully staffed engineering department for custom applications

Specifications

- Mounting heights varies from model to model D6073: 46 1/4" - 50" D6073x-4: 38 1/4" - 48" D6073x: 40 - 50"
- Up to 2,150 PSI required for 400 lb load
- 6-8 second cycle time @ 3 GPM
- 45 degree dump angle
- Two-piece faceplate for easy removal
- Safety Yellow powder-coated finish
- Self-Lubricated bearings at pivot points
- Easy bolt-on/off mounting plate included
- Adjustable flow control valve
- New 3 year limited warranty


Inside rack & pinion systems, the loads are concentrated on only one tooth





actuator, the loads





Pictured: D6073x for deeper dumping

NEW ADVANCED 27K ACTUATOR

- Higher torque & lower weight
- Two-part casted body is easier to open and service
 - Fewer parts & fewer points that need sealing
- New grease points positioned to help flush away contaminants

Perkins Manufacturing Company

737 Oakridge Drive Romeoville, IL 60446 (708) 482-9500 Fax: (708) 354-5878 Email: tuckaway@perkinsmfg.com

Perkins. Route tested. Driver approved.